

# INTERNATIONAL MIRROR CLASS



The following amendments to the Class Rules have been approved to be effective 30<sup>th</sup> August 2012 by the Class Rules Sub committee.

## Rule 6.1 - Standing Rigging

### Amendment:

6.1.1 Only the following standing rigging of wire rope not less than 2mm diameter shall be fitted:

- One forestay
- Two shrouds
- One jib halyard strop

Boats with bermuda masts may omit the jib halyard strop. All standing rigging shall be attached to the gunter

6.1.2 All standing rigging shall be attached to the gunter mast by being looped over the top of the mast not more than 50mm from its top. A plastic or GRP cap to protect the gunter mast from the rigging is permitted.

6.1.3 The forestay shall be attached to the forestay attachment fitting. ~~The method of attachment is optional.~~

6.1.4 The method of attachment of the **forestay** shall be

- (i) directly to the forestay attachment fitting
- (ii) by a rigging adjuster plate or link.
- (iii) by a rigging screw
- (iv) by a shackle or shackles
- (v) by rigging which may include a purchase, blocks and a cleat which shall be attached to the **forestay** attachment fitting or the **forestay** only.

~~6.1.4 Each shroud shall be attached to a shroud attachment fitting. The method of attachment is optional but Highfield levers are not permitted.~~

6.1.5 Each **shroud** shall be attached to one of the **shroud** plate fittings identified in rule 1.7.1.

6.1.6 The method of attachment of the **shrouds** shall be

- (i) directly to the shroud plate fitting
- (ii) by a rigging adjuster plate or link
- (iii) by a shackle or shackles
- (iv) by a rigging screw

~~6.1.57 The **shrouds and forestay** tension and the length of the **shrouds and forestay** shall not be altered while racing.~~

---